

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) An airport display device, comprising:

a display including at least one window;

a database including data related to an airport;

a selector configured to select from a plurality of different degrees of zoom a degree of zoom for the an airport image to be displayed, the airport image corresponding to the airport from a plurality of different degrees of zoom, the selector comprising a plurality of zoom buttons configured to display the airport image in the window according to a plurality of predefined zoom degrees;

a control unit connected to the display, the database, and the selector, the control unit being and configured to control the display to display in the at least one window the airport image according to a scale value representative of the degree of zoom selected by the selector; and

a changing unit configured to change the scale value representative of the degree of zoom.

2. (Currently Amended) The airport display device according to claim 1, wherein:

the selector includes [[a]] at least one zoom button configured to zoom in and zoom out between a maximum zoom value and a minimum zoom value so as to display different detailed views of the airport.

3. (Currently Amended) The airport display device according to claim 1, wherein the selector includes:

a first button configured to display the airport image in the window according to a first predefined zoom degree corresponding to general navigation, the airport image corresponding to the first predefined zoom degree including a full display of the airport;

a second button configured to display the airport image in the window according to a second predefined zoom degree corresponding to proximity navigation, the airport image corresponding to the second predefined zoom degree including a plurality of details of the airport; and

a third button configured to display the airport image in the window according to a third predefined zoom degree corresponding to airport details, the airport image corresponding to the third predefined zoom degree including details of the airport required for precision taxiing.

4. (Currently Amended) The airport display device according to claim 1, wherein:
the display system is installed in a moving airport vehicle; [[,]] and
~~wherein~~ the selector includes a centering button configured to automatically reconfigure the display such that the moving vehicle is displayed in a center of the window.

5. (Currently Amended) The airport display device according to claim 1, wherein:
the selector includes a selection mechanism configured to display predefined portions of the airport in a cyclic manner based on selections of the selection mechanism.

6. (Currently Amended) The airport display device according to claim 1, wherein:
the selector includes a toggle button configured to automatically display in the airport image the entire airport on the window upon selection of the toggle button and to redisplay in

the airport image a portion of the airport image being displayed prior to selection of the toggle button upon another selection of the toggle button.

7. (Currently Amended) The airport display device according to claim 1, wherein:
the selector includes a selection mechanism configured to select a portion of the airport such that the portion of the airport is displayed in the airport image on the window.

8. (Currently Amended) The airport display device according to claim 1, wherein:
the selector includes a displacement button configured to displace a view of the airport being displayed in the airport image on the window in horizontal and vertical directions so as to display other portions of the airport.

9. (Currently Amended) The airport display device according to claim 1 ~~claim 1~~,
wherein:
the control unit is configured to display two different degrees of zoom in a continuous manner such that a change from the first degree of zoom to the second degree of zoom appears continuous to an operator viewing the display.

10. (Currently Amended) An airport display system, comprising:
a display including at least one window;
means for storing data related to an airport;
means for selecting from a plurality of different degrees of zoom a degree of zoom for ~~the an~~ an airport image to be displayed, the airport image corresponding to the airport ~~from a plurality of different degrees of zoom, the means for selecting comprising a plurality of zoom~~

buttons configured to display the airport image in the window according to a plurality of predefined zoom degrees;

means for controlling the display to display in the at least one window the airport image according to a scale value representative of the degree of zoom selected by the selecting means, said controlling means being connected to the display, the storing means, and the selecting means; and

means for changing the scale value representative of the degree of zoom.

11. (Currently Amended) The airport display system according to claim ~~[[1]]~~ 10, wherein:

the selecting means includes ~~[[a]]~~ at least one means for zooming in and zooming out between a maximum zoom value and a minimum zoom value so as to display different detailed views of the airport.

12. (Currently Amended) The airport display system according to claim ~~[[1]]~~ 10, wherein the selecting means includes:

a first means for displaying the airport image in the window according to a first predefined zoom degree corresponding to general navigation, the airport image corresponding to the first predefined zoom degree including a full display of the airport;

a second means for displaying the airport image in the window according to a second predefined zoom degree corresponding to proximity navigation, the airport image corresponding to the second predefined zoom degree including a plurality of details of the airport; and

a third means for displaying the airport image in the window according to a third predefined zoom degree corresponding to airport details, the airport image corresponding to

the third predefined zoom degree including details of the airport required for precision taxiing.

13. (Currently Amended) The airport display system according to claim [[1]] 10,
wherein:

the display system is installed in a moving airport moving vehicle; [[,]] and
~~wherein~~ the selecting means includes a means for automatically reconfiguring the
display such that the moving vehicle is displayed in a center of the window.

14. (Currently Amended) The airport display system according to claim [[1]] 10,
wherein:

the selecting means includes a means for displaying predefined portions of the airport
in a cyclic manner based on selections of the displaying means.

15. (Currently Amended) The airport display system according to claim [[1]] 10,
wherein:

the selecting means includes a means for automatically displaying in the airport image
the entire airport on the window upon selection of the automatically displaying means and for
redisplaying in the airport image a portion of the airport image being displayed prior to
selection of the automatically displaying means upon another selection of the automatically
displaying means.

16. (Currently Amended) The airport display system according to claim [[1]] 10,
wherein:

the selecting means includes a portion means for selecting a portion of the airport such that the portion of the airport is displayed in the airport image on the window.

17. (Currently Amended) The airport display system according to claim ~~[[1]]~~ 10, wherein:

the selecting means includes a means for displacing a view of the airport being displayed in the airport image on the window in horizontal and vertical directions so as to display other portions of the airport.

18. (Currently Amended) The airport display system according to claim 10 ~~claim 1~~, wherein:

the controlling means displays two different degrees of zoom in a continuous manner such that a change from the first degree of zoom to the second degree of zoom appears continuous to an operator viewing the display.

19. (New): The airport display device according to claim 1, further comprising:
an updating mechanism configured to dynamically update in real-time the database according to traffic of airport vehicles including aircrafts or technical vehicles.

20. (New): The airport display device according to claim 19, wherein:
the airport vehicles are displayed on the airport image and identified by a sign, a code, or a number.

21. (New): The airport display device according to claim 19, wherein:
the airport display device is arranged in an aircraft; and

the updating mechanism is configured to update the database using digital transmission links between the aircraft and a station located on a ground of the airport.

22. (New): The airport display device according to claim 1, wherein:

the airport display device is integrated in a portable computer; and

the portable computer is installed in a piloting position in an aircraft.

23. (New): The airport display system according to claim 10, further comprising:

an updating means configured to dynamically update in real-time the means for storing data according to traffic of airport vehicles including aircrafts or technical vehicles.

24. (New): The airport display system according to claim 23, wherein:

the airport vehicles are displayed on the airport image and identified by a sign, a code, or a number.

25. (New): The airport display system according to claim 23, wherein:

the airport display device is arranged in an aircraft; and

the updating means is configured to update the means for storing data using digital transmission links between the aircraft and a station located on a ground of the airport.

26. (New): The airport display system according to claim 10, wherein:

the airport display device is integrated in a portable computing means; and

the portable computing means is installed in a piloting position in an aircraft.